



DOPPEN 1/2" 12-KANT, INCH-MATEN



Kenmerken

- OGV® profiel: grotere krachtoverbrenging zonder de moer te beschadigen
- Uitvoering: glanzend verchromd
- Verkrijgbaar als set op een metalen rek: Ref S.40U (3/8" --> 21/32") en Ref S.41U (11/16" --> 1")



Varianten (19)

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte (inch) |
|---------------|-------------------------|----------------------|
| 41-10451-704 | S.1P | 1 |
| 41-10451-706 | S1.P1/16 | 1'1/16 |
| 41-10451-708 | S.1P1/8 | 1'1/8 |
| 41-10451-710 | S.1P3/16 | 1'3/16 |
| 41-10450-534 | S.1P1/4 | 1'1/4 |
| 41-10155-431 | S.3/8 | 3/8 |
| 41-10155-432 | S.7/16 | 7/16 |
| 41-10155-433 | S.1/2 | 1/2 |
| 41-10155-434 | S.9/16 | 9/16 |
| 41-10155-435 | S.19/32 | 19/32 |
| 41-10155-436 | S.5/8 | 5/8 |
| 41-10155-437 | S.21/32 | 21/32 |
| 41-10155-438 | S.11/16 | 11/16 |
| 41-10155-439 | S.3/4 | 3/4 |

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte (inch) |
|----------------------|--------------------------------|-----------------------------|
| 41-10155-440 | S.25/32 | 25/32 |
| 41-10155-441 | S.13/16 | 13/16 |
| 41-10155-442 | S.7/8 | 7/8 |
| 41-10155-443 | S.15/16 | 15/16 |
| 41-10155-444 | S.31/32 | 31/32 |