



DOPPEN 1/2" 12-KANT, METRISCH



Kenmerken

- OGV® profiel: grotere krachtoverbrenging zonder de moer te beschadigen
- Uitvoering: glanzend verchroom
- Verkrijgbaar op metalen rek: Ref S.40E (8 --> 16 mm) en Ref S.41E (17 --> 24 mm)



Varianten (26)

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte (mm) |
|---------------|-------------------------|--------------------|
| 41-10155-526 | S.8 | 8 |
| 41-10155-527 | S.9 | 9 |
| 41-10155-528 | S.10 | 10 |
| 41-10155-529 | S.11 | 11 |
| 41-10155-530 | S.12 | 12 |
| 41-10155-531 | S.13 | 13 |
| 41-10155-532 | S.14 | 14 |
| 41-10155-533 | S.15 | 15 |
| 41-10155-534 | S.16 | 16 |
| 41-10155-535 | S.17 | 17 |
| 41-10155-536 | S.18 | 18 |
| 41-10155-537 | S.19 | 19 |
| 41-10155-538 | S.20 | 20 |
| 41-10155-539 | S.21 | 21 |

| Artikelnummer | Artikelnummer fabrikant | Sleutelwijdte (mm) |
|----------------------|--------------------------------|---------------------------|
| 41-10155-540 | S.22 | 22 |
| 41-10155-541 | S.23 | 23 |
| 41-10155-542 | S.24 | 24 |
| 41-10155-543 | S.25 | 25 |
| 41-10155-544 | S.26 | 26 |
| 41-10155-545 | S.27 | 27 |
| 41-10155-546 | S.28 | 28 |
| 41-10155-547 | S.29 | 29 |
| 41-10155-548 | S.30 | 30 |
| 41-10155-549 | S.31 | 31 |
| 41-10155-550 | S.32 | 32 |
| 41-10155-551 | S.34 | 34 |