



HANDTAP BSW, 3E TAP



Omschrijving

Kenmerken

- 3e Handtap BSW BS 84
- Din 352
- HSS-G



Varianten (26)

Artikelnummer	Schroefdraad	Schroefdraad	Taplengte	Kolfdiameter	Taplengte	Tapdiepte	Opname (mm)	Speed
41-10207-509	Bsw 1/16	Bsw 1/16	36,0	2,5	36,0	10,0	2,1	60
41-10207-513	Bsw 3/32	Bsw 3/32	36,0	2,8	36,0	10,0	2,1	48
41-10207-517	Bsw 1/8	Bsw 1/8	40,0	3,5	40,0	12,0	2,7	40
41-10207-521	Bsw 5/32	Bsw 5/32	45,0	4,5	45,0	14,0	3,4	32
41-10207-525	Bsw 3/16	Bsw 3/16	50,0	6,0	50,0	18,0	4,9	24
41-10207-529	Bsw 7/32	Bsw 7/32	50,0	6,0	50,0	18,0	4,9	24
41-10207-533	Bsw 1/4	Bsw 1/4	50,0	6,0	50,0	19,0	4,9	20
41-10207-537	Bsw 5/16	Bsw 5/16	56,0	6,0	56,0	22,0	4,9	18
41-10207-541	Bsw 3/8	Bsw 3/8	70,0	7,0	70,0	24,0	5,5	16
41-10207-545	Bsw 7/16	Bsw 7/16	70,0	8,0	70,0	24,0	6,2	14
41-10207-549	Bsw 1/2	Bsw 1/2	75,0	9,0	75,0	29,0	7,0	12
41-10207-553	Bsw 9/16	Bsw 9/16	80,0	11,0	80,0	30,0	9,0	12
41-10207-557	Bsw 5/8	Bsw 5/8	80,0	12,0	80,0	32,0	9,0	11
41-10207-561	Bsw 3/4	Bsw 3/4	95,0	14,0	95,0	40,0	11,0	10
41-10207-565	Bsw 7/8	Bsw 7/8	100,0	18,0	100,0	40,0	14,5	9
41-10207-569	Bsw 1" 4550"	Bsw 1" 4550"	110,0	18,0	110,0	50,0	14,5	8

Artikelnummer	Schroefdraad	Schroefdraad	Taplengte	Kolfdiameter	Taplengte	Tapdiepte	Opname (mm)	Speed
41-10207-573	Bsw 1.1/8	Bsw 1.1/8	132,0	22,0	132,0	56,0	18,0	7
41-10207-577	Bsw 1.1/4	Bsw 1.1/4	132,0	22,0	132,0	56,0	18,0	7
41-10207-581	Bsw 1.3/8	Bsw 1.3/8	150,0	28,0	150,0	63,0	22,0	6
41-10207-585	Bsw 1.1/2	Bsw 1.1/2	150,0	32,0	150,0	63,0	24,0	6
41-10207-589	Bsw 1.5/8	Bsw 1.5/8	160,0	32,0	160,0	70,0	24,0	5
41-10207-593	Bsw 1.3/4	Bsw 1.3/4	160,0	36,0	160,0	70,0	29,0	5
41-10207-597	Bsw 1.7/8	Bsw 1.7/8	190,0	36,0	190,0	80,0	29,0	4.1/2
41-10207-601	Bsw 2" 4562"	Bsw 2" 4562"	190,0	40,0	190,0	80,0	32,0	4.1/2
41-10218-337	Bsw 2.1/4	Bsw 2.1/4	220,0	45,0	220,0	80,0	35,0	4
41-10218-341	Bsw 2.1/2	Bsw 2.1/2	220,0	50,0	220,0	80,0	39,0	4