



## HANDTAP G(BSP), 1E TAP



### Omschrijving

#### Kenmerken

- 1e Handtap G (BSP)
- Din 5157
- HSS-G



### Varianten (21)

Artikelnummer	Schroefdraad	Schroefdraad	Taplengte	Kolfdiameter	Taplengte	Tapdiepte	Opname (mm)	Spoed
41-10207-603	G 1/8	G 1/8	63,0	7,0	63,0	20,0	5,5	28
41-10207-606	G 1/4	G 1/4	70,0	11,0	70,0	22,0	9,0	19
41-10207-609	G 3/8	G 3/8	70,0	12,0	70,0	22,0	9,0	19
41-10207-612	G 1/2	G 1/2	80,0	16,0	80,0	22,0	12,0	14
41-10207-615	Bsp 3/8	Bsp 3/8	80,0	18,0	80,0	22,0	14,5	14
41-10207-618	G 3/4	G 3/4	90,0	20,0	90,0	22,0	16,0	14
41-10207-621	G 7/8	G 7/8	90,0	22,0	90,0	22,0	18,0	14
41-10207-624	G 1" 4792"	G 1" 4792"	100,0	25,0	100,0	25,0	20,0	11
41-10207-627	G 1.1/8	G 1.1/8	125,0	28,0	125,0	40,0	22,0	11
41-10207-630	G 1.1/4	G 1.1/4	125,0	32,0	125,0	40,0	24,0	11
41-10207-633	G 1.3/8	G 1.3/8	140,0	36,0	140,0	40,0	29,0	11
41-10207-636	G 1.1/2	G 1.1/2	140,0	36,0	140,0	40,0	29,0	11
41-10207-639	G 1.5/8	G 1.5/8	140,0	40,0	140,0	40,0	32,0	11
41-10207-642	G 1.3/4	G 1.3/4	140,0	40,0	140,0	40,0	32,0	11
41-10207-645	G 2" 4804"	G 2" 4804"	160,0	45,0	160,0	40,0	35,0	11
41-10207-648	G 2.1/4	G 2.1/4	160,0	50,0	160,0	40,0	39,0	11
41-10207-651	G 2.1/2	G 2.1/2	160,0	50,0	160,0	40,0	39,0	11

Artikelnummer	Schroefdraad	Schroefdraad	Taplengte	Kolfdiameter	Taplengte	Tapdiepte	Opname (mm)	Spoed
41-10207-654	G 2.3/4	G 2.3/4	160,0	50,0	160,0	40,0	39,0	11
41-10207-657	G 3" 4808"	G 3" 4808"	160,0	50,0	160,0	40,0	39,0	11
41-10207-660	G 3.1/2	G 3.1/2	180,0	56,0	180,0	45,0	44,0	11
41-10207-663	G 4" 4812"	G 4" 4812"	180,0	56,0	180,0	45,0	44,0	11