



## HANDTAP UNC, 3E TAP

# GUHRING



### Kenmerken

- Handtap, UNC, 3e tap
- DIN 352
- Snijrichting rechts
- Type N
- Materiaal HSS
- Voorsnijder (1e tap)
- Standaard 2 DIN 2184-2

### Varianten (10)

Artikelnummer	Artikelnummer fabrikant	Schroefdraad	Spoed	Kolfdiameter	Taplengte
41-10425-275	984-2,184 (9009840021840)	UNC 2 - 56	0,454	2,8	13
41-10425-276	984-4 (00984 002845)	UNC 4 - 40	0,635	3,5	14
41-10425-277	984-6 (9009840035050)	UNC 6 - 32	0,794	4,0	16
41-10425-278	984-8 (9009840041660)	UNC 8 - 32	0,794	4,5	17
41-10425-279	984-12 (9009840054860)	UNC 12 - 24	1,058	6,0	23
41-10425-280	984-1/4 (9009840063500)	UNC 1/4" - 20	1,270	6,0	23
41-10425-281	984-5/16 (9009840079380)	UNC 5/16" - 18	1,411	6,0	28
41-10425-282	984-3/8 (9009840095250)	UNC 3/8" - 16	1,587	7,0	32
41-10425-283	984-7/16 (9009840111130)	UNC 7/16" - 14	1,814	8,0	32
41-10425-284	984-1/2 (9009840127000)	UNC 1/2" - 13	1,954	9,0	36